

常州市创联电源科技股份有限公司

Changzhou Chuanglian Power Supply Techology Corperation

承认书

CERTIFICATE FOR CONFIRMATION

客户名称 (CUSTOMER) :	
客户料号 (PART NO.) :	
产品名称 (PART NAME) :	Switching Power Supply
产品规格 (DESCRIPTION) :	A-75FAM
编制日期 (DATE) :	

制定 (Engineer)	审核 (Supervisor)	核准 (Engineer Manager)
承认 (Engineer)	审核 (Supervisor)	核准 (Engineer Manager)

注:此承认书一式二份, 请签核完后寄回我司一份保存。
Remark:This certification is in duplicate,please send us a copy signing.

厂商: 常州市创联电源科技股份有限公司 地址:江苏省常州市钟楼经济开发区童子河西路8号 电话:86-519-85215050, 85210525 传真:86-519-85215252, 85215770 网址:www.haitaik.com 邮箱:ad@haitaik.com	Mfr.:Changzhou Chuanglian Power Supply Tech Corp Address:No.8,Tongzihe West Road,Zhonglou Economic Development Zone,Changzhou,Jiangsu 213024,China Tel:86-519-85215050, 85210525 Fax:86-519-85215252, 85215770 Web:www.haitaik.com E-mail:ad@haitaik.com
---	---

编号:



A-75FAM Switching Power Supply



◆ Feature

- Universal AC input
- No load power consumptin<0.3W
- Protections: short circuit/overload
- Cooling by free air convection
- 100% pass aging test
- 3 years warranty



General Specification

ModelNo.		A-75FAM-5	A-75FAM-12	A-75FAM-24	A-75FAM-36	A-75FAM-48
Output	DC voltage	5V	12V	24V	36V	48V
	Rated current	14A	6A	3.2A	2.1	1.6A
	Current Range	0~14A	0~6A	0~3.2A	0~2.1A	0~1.6A
	Rated power	70W	72W	76.8W	75.6W	76.8W
	Ripple & Noise	120mVp-p	120mVp-p	150mVp-p	200mVp-p	200mVp-p
	Voltage regulation range	±10.0%				
	Voltage accuracy	±1.0%				
	Line regulation	±0.5%				
	Load adjustment rate	±0.5%				
	Rise	500ms, 30ms/230VAC Full Load				
	Hold up time (Typ)	60ms/230VAC 12ms/115VAC Full Load				
Input	Voltage range	100~240VAC;				
	Frequency	47~63HZ				
	PFC (Typ)					
	Efficiency (Typ)	85%	88%	90%	92%	92%
	Alternating current	1.4A/115VAC, 0.85A/230V				
	Inrush current (Typ)	50A/230VAC				
	Leakage current	<3.5mA/240VAC				
Protect ions	Overload	110~150% of rated output				
	Short circuit	Hiccup mode, auto-recovery				
	Over Voltage	115%-135% rated output voltage, constant voltage limited				
Envirom ent	Working temp.	-30℃~+50℃ (refer to output derating curve)				
	Working humidity	10~95%RH non condensing				
	Storage temp.	-40℃~+85℃				
	Storage humidity	10~95%RH non condensing				
	temp. coefficient	±0.03%/℃ (0~50℃)				
	Vibration resistance	10~500Hz, 2G, 10min/cycle, X、Y、Z 60min in each direction				
Safety	Safety standards	design according to GB4943-2001, UL1012				
	withstand voltage	I/P-O/P:3KV AC、I/P-FG: 2KV AC、O/P-FG: 0.5KV AC				
	Isolation Resistance	I/P-O/P、I/P-FG、O/P-FG: 100MΩ /500VDC				
	EMC	EN55022 CLASS B				
Others	Lifetime	100,000 hours(25℃)				
	Size	99×97×30 (L*W*H)				
	Weight	0.3Kg/pc				
Rmarks	*In order to extend the service life, it is recommended to leave 30% more allowance when loading. For example, if the equipment needs 100W power, please choose the power supply over 130W. *Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uF & 47uF parallel capacitor					

a v. lui & trei paraleli capacitori.



Load temperature drop curve




Installation

警示

Warning


- 使用安装螺丝M3*6mm,
Using the mounting screws M3*6mm
- 深入外壳螺丝深度MAX 4mm,
Deep housing screw depth Max 4mm
- 详见右图
As shown on the right





A-75FAM Switching Power Supply

Drawing:



Pin No.	Assignment	Pin No.	Assignment
1	AC/L	4	DC output (V-)
2	AC/N	5	DC output (V+)
3	FG		